

OSHA 1926.1153 – Respirable Silica

TABLE I: SPECIFIED EXPOSURE CONTROL METHODS WHEN WORKING WITH MATERIALS CONTAINING CRYSTALLINE SILICA

Equipment/Task	Engineering and work practice control methods	Required Respiratory Protection and Minimum Assigned Protection Factor (APF)	
		≤ 4 hr/shift	> 4 hr/shift
(i) Stationary masonry saws	Use saw equipped with integrated water delivery system that continuously feeds water to the blade.	None	None
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
(ii) Handheld power saws (any blade diameter)	Use saw equipped with integrated water delivery system that continuously feeds water to the blade.	None	APF 10
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	- When used outdoors		
	- When used indoors or in an enclosed area.		
(iii) Handheld power saws for cutting fiber-cement board (with blade diameter of 8 inches or less)	For tasks performed outdoors only:	None	None
	Use saw equipped with commercially available dust collection system.		
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency.		
(iv) Walk-behind saws	Use saw equipped with integrated water delivery system that continuously feeds water to the blade.	None	None
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	- When used outdoors		
	- When used indoors or in an enclosed area.		
(v) Drivable saws	For tasks performed outdoors only:	None	None
	Use saw equipped with integrated water delivery system that continuously feeds water to the blade.		
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
(vi) Rig - mounted core saws or drills	Use saw equipped with integrated water delivery system that continuously feeds water to the blade.	None	None
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		

Equipment/Task	Engineering and work practice control methods	Required Respiratory Protection and Minimum Assigned Protection Factor (APF)	
		≤ 4 hr/shift	> 4 hr/shift
(vii) Handheld and stand-mounted drills (including impact and rotary hammer drills)	Use drill equipped with commercially available shroud or cowling with dust collection system.	None	None
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.		
	Use a HEPA-filtered vacuum when cleaning holes.		
(viii) Dowel drilling rigs for concrete	For tasks performed outdoors only:	APF 10	APF 10
	Use shroud around drill bit with a dust collection system. Dust collector must have a filter with 99% or greater efficiency and a filter-cleaning mechanism.		
	Use a HEPA-filtered vacuum when cleaning holes.		
(ix) Vehicle-mounted drilling rigs for rock and concrete	Use dust collection system with close capture hood or shroud around drill bit with a low-flow water spray to wet the dust at the discharge point from the dust collector.	None	None
	OR Operate from within an enclosed cab and use water for dust suppression on drill bit	None	None
(x) Jackhammers and handheld powered chipping tools	Use tool with water delivery system that supplies a continuous stream or spray of water at the point of impact.		
	- When used outdoors	None	APF 10
	- When used indoors or in an enclosed area.	APF 10	APF 10
	OR		
	Use tool equipped with commercially available shroud and dust collection system.		
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.		
	- When used outdoors	None	APF 10
- When used indoors or in an enclosed area.	APF 10	APF 10	
(xi) Handheld grinders for mortar removal (i.e., tuckpointing)	Use grinder equipped with commercially available shroud and dust collection system.	APF 10	APF 25
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.		

Equipment/Task	Engineering and work practice control methods	Required Respiratory Protection and Minimum Assigned Protection Factor (APF)	
		≤ 4 hr/shift	> 4 hr/shift
(xii) Handheld grinders for uses other than mortar removal	For tasks performed outdoors only:		
	Use grinder equipped with integrated water delivery system that continuously feeds water to the grinding surface.	None	None
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	OR		
	Use grinder equipped with commercially available shroud and dust collection system.		
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	Dust collector must provide 25 cubic feet per minute (cfm) or greater of airflow per inch of wheel diameter and have a filter with 99% or greater efficiency and a cyclonic pre-separator or filter-cleaning mechanism.		
	- When used outdoors	None	None
- When used indoors or in an enclosed area.	None	APF 10	
(xiii) Walk-behind milling machines and floor grinders	Use machine equipped with integrated water delivery system that continuously feeds water to the cutting surface.	None	None
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	OR		
	Use machine equipped with dust collection system recommended by the manufacturer		
	Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.		
	Dust collector must provide the air flow recommended by the manufacturer, or greater, and have a filter with 99% or greater efficiency and a filter-cleaning mechanism.		
When used indoors or in an enclosed area, use a HEPA-filtered vacuum to remove loose dust in between passes.	None	None	
(xiv) Small drivable milling machines (less than half-lane)	Use a machine equipped with supplemental water sprays designed to suppress dust. Water must be combined with a surfactant.	None	None
	Operate and maintain machine to minimize dust emissions.		

Equipment/Task	Engineering and work practice control methods	Required Respiratory Protection and Minimum Assigned Protection Factor (APF)	
		≤ 4 hr/shift	> 4 hr/shift
(xv) Large drivable milling machines (half-lane and larger)	For cuts of any depth on asphalt only:		
	Use machine equipped with exhaust ventilation on drum enclosure and supplemental water sprays designed to suppress dust.	None	None
	Operate and maintain machine to minimize dust emissions.		
	For cuts of four inches in depth or less on any substrate:		
	Use machine equipped with exhaust ventilation on drum enclosure and supplemental water sprays designed to suppress dust.	None	None
	Operate and maintain machine to minimize dust emissions.		
	OR		
	Use a machine equipped with supplemental water spray designed to suppress dust. Water must be combined with a surfactant.	None	None
	Operate and maintain machine to minimize dust emissions.		
(xvi) Crushing machines	Use equipment designed to deliver water spray or mist for dust suppression at crusher and other points where dust is generated (e.g., hoppers, conveyers, sieves/sizing or vibrating components, and discharge points).		
	Operate and maintain machine in accordance with manufacturer's instructions to minimize dust emissions.	None	None
	Use a ventilated booth that provides fresh, climate-controlled air to the operator, or a remote control station.		
(xvii) Heavy equipment and utility vehicles used to abrade or fracture silica-containing materials (e.g., hoe-ramming, rock ripping) or used during demolition activities involving silica-containing materials	Operate equipment from within an enclosed cab.	None	None
	When employees outside of the cab are engaged in the task, apply water and/or dust suppressants as necessary to minimize dust emissions.	None	None
(xviii) Heavy equipment and utility vehicles for tasks such as grading and excavating but not including: demolishing, abrading, or fracturing silica-containing materials	Apply water and/or dust suppressants as necessary to minimize dust emissions.	None	None
	OR		
	When the equipment operator is the only employee engaged in the task, operate equipment from within an enclosed cab.	None	None